

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Trade name : Threadlocker Red 120 0.34 fl oz
 Product code : 78072720034-0

1.2. Recommended use and restrictions on use

Recommended use : Anaerobic adhesive for locking

1.3. Supplier

Distributor

Saint-Gobain Abrasives, Inc.
 1 New Bond Street
 Worcester, MA 01615
 - United States of America (USA)
 T 800-551-4413
www.Nortonabrasives.com

1.4. Emergency telephone number

Emergency number : 508-795-5000
 CHEMTRAC: For emergencies in the US and Canada
 call: 800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4	H227 Combustible liquid
Organic Peroxide Category E	H242 Heating may cause a fire.
Skin corrosion/irritation Category 1	H314 Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318 Causes serious eye damage
Skin sensitization, Category 1	H317 May cause an allergic skin reaction
Specific target organ toxicity (repeated exposure) Category 2	H373 May cause damage to organs through prolonged or repeated exposure (oral, Inhalation, Dermal)

Full text of H statements: see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H227 - Combustible liquid
 H242 - Heating may cause a fire.
 H314 - Causes severe skin burns and eye damage
 H317 - May cause an allergic skin reaction
 H318 - Causes serious eye damage
 H373 - May cause damage to organs through prolonged or repeated exposure (oral, Inhalation, Dermal)

Precautionary statements (GHS US) :

P101 - If medical advice is needed, have product container or label at hand.
 P102 - Keep out of reach of children.
 P201 - Obtain special instructions before use.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P220 - Keep/Store away from combustible materials
 P234 - Keep only in original container.
 P261 - Avoid breathing vapors, gas, spray.
 P264 - Wash hands thoroughly after handling.
 P272 - Contaminated work clothing must not be allowed out of the workplace.
 P280 - Wear protective clothing, eye protection, face protection, protective gloves.
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

Threadlocker Red 120 0.34 fl oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P302+P352 - If on skin: Wash with plenty of soap and water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P370+P378 - In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P410 - Protect from sunlight.
P420 - Store away from other materials.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Saccharin	(CAS-No.) 81-07-2	0 - 10	Skin Corr. 1, H314 Eye Dam. 1, H318
epoxy resins, solids	(CAS-No.) 25068-38-6	0 - 10	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
Cumene hydroperoxide	(CAS-No.) 80-15-9	0 - 5	Flam. Liq. 4, H227 Org. Perox. E, H242 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT RE 2, H373

Full text of hazard classes and H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : If medical advice is needed, have product container or label at hand.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for several minutes. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Get immediate medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : May cause an allergic skin reaction.
- Symptoms/effects after eye contact : May cause severe irritation. redness, itching, tears.
- Symptoms/effects after ingestion : May be harmful if swallowed. Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

Threadlocker Red 120 0.34 fl oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Dry chemical, CO₂, or water spray or regular foam.
Unsuitable extinguishing media : High pressure water jet.

5.2. Specific hazards arising from the chemical

- Fire hazard : No direct explosion hazard.
Explosion hazard : No available data.
Reactivity in case of fire : No data available.

5.3. Special protective equipment and precautions for fire-fighters

- Precautionary measures fire : Use necessary protective equipment to avoid the risk of contact with hands, skin, eyes and respiratory tract.
Firefighting instructions : In case of fire: Stop leak if safe to do so. Fight fire with normal precautions from a reasonable distance. Cool laterally with water containers exposed to flames, even after the fire is extinguished.
Protection during firefighting : Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Do not handle until all safety precautions have been read and understood. Stop leak if safe to do so. Avoid contact with skin and eyes.

6.1.1. For non-emergency personnel

- Protective equipment : Use necessary protective equipment to avoid the risk of contact with hands, skin, eyes and respiratory tract.
Emergency procedures : Notify fire brigade and environmental authorities. In case of spillage or leakage in large quantities, isolate the area.

6.1.2. For emergency responders

- Protective equipment : Use personal protective equipment as required. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Absorb and / or contain the spill with an inert material (sand or peat), then place it in a suitable container.

6.2. Environmental precautions

Harmful to aquatic life with long lasting effects.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with barriers or absorbents in order to avoid their transposition and entry into pipes and sewers. Contain large spillage with sand or earth.
Methods for cleaning up : In case of small spills, clean with paper towels and put in containers for final disposal. In case of large spills, use inert absorbent material and place in sealed containers, duly identified, for later final disposal. Ventilate the area.

6.4. Reference to other sections

See Heading 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Keep only in original container.
Handling temperature : ≈ 15 - 35 °C Store in a well-ventilated place.
Hygiene measures : Wear personal protective equipment. Do not eat, drink or smoke when using this product. Wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep only in original packaging.
Storage conditions : Keep cool. Protect from sunlight. Store in a well-ventilated place.
Incompatible products : Incompatible products are metals, as they can cure the product.
Storage temperature : Do not return the waste materials to the containers as the contamination may reduce the shelf life of the product in bulk.

Threadlocker Red 120 0.34 fl oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage area : Store in a well-ventilated place.
Special rules on packaging : Do not reuse the packaging used.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Threadlocker Red 120 0.34 fl oz	
No additional information available	
Cumene hydroperoxide (80-15-9)	
No additional information available	
Saccharin (81-07-2)	
No additional information available	
epoxy resins, solids (25068-38-6)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	3 mg/m ³ (Respirable fraction)

8.2. Appropriate engineering controls

Appropriate engineering controls : Emergency eye wash and safety shower devices must be available in the immediate vicinity of any possible exposure.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Use the recommended personal protective equipment.

Hand protection:

PVC protective gloves.

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Ensure adequate ventilation. If used in a poorly ventilated place, an approved respirator or mask that has a filter for organic vapors must be used

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : red
Odor : Characteristic
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : > 150 °C
Flash point : > 93 °C
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Vapor pressure : No data available
Relative vapor density at 20 °C : No data available
Relative density : No data available
Specific gravity / density : 1.12 g/ml
Solubility : Soluble in MEK (Methyl ethyl ketone).

Threadlocker Red 120 0.34 fl oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 6000 - 8000 cP
Explosion limits	: No data available
Explosive properties	: No data available.
Oxidizing properties	: No data available.

9.2. Other information

VOC content	: Less than 3% (w/w)
-------------	----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Organic peroxides.

10.2. Chemical stability

Stable under normal conditions of use.

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

Excessive heat.

10.5. Incompatible materials

Strong oxidizing substances.

10.6. Hazardous decomposition products

Toxic fumes may arise when incinerated: Carbon Oxides, Sulfur Oxides, Nitrogen Oxides and irritating organic Vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Cumene hydroperoxide (80-15-9)	
LD50 oral rat	382 mg/kg (Rat, Male, Experimental value, Oral)
LD50 dermal rat	1200 - 1520 mg/kg body weight (Rat, Male/ female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	1.37 mg/l (4 h, Rat, Male, Experimental value, Inhalation)
LC50 inhalation rat (ppm)	220 ppm Animal: rat, Animal sex: male
ATE US (oral)	382 mg/kg body weight
ATE US (dermal)	1200 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	1.37 mg/l/4h
ATE US (dust, mist)	1.37 mg/l/4h

Saccharin (81-07-2)	
LD50 oral rat	8440 - 9710 mg/kg body weight Animal: rat, Guideline: other:
LD50 dermal rabbit	4694 mg/kg body weight Animal: rabbit, Guideline: other: Federal Hazards Substances Act (Revised Federal Register Sept 17 1964)
LC50 inhalation rat (mg/l)	815.265 mg/l air Animal: rat, Guideline: other: OECD Guideline 403 (Acute Inhalation Toxicity)
ATE US (oral)	8440 mg/kg body weight
ATE US (dermal)	4694 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Threadlocker Red 120 0.34 fl oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Saccharin (81-07-2)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure (oral, Inhalation, Dermal).

Cumene hydroperoxide (80-15-9)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Saccharin (81-07-2)	
LOAEL (oral, rat, 90 days)	1666.66 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other:
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause severe irritation. redness, itching, tears.
Symptoms/effects after ingestion	: May be harmful if swallowed. Burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

SECTION 12: Ecological information

12.1. Toxicity

Cumene hydroperoxide (80-15-9)	
LC50 fish 1	3.9 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, <i>Oncorhynchus mykiss</i> , Semi-static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	18.84 mg/l (OECD 202: Daphnia sp. Acute Immobilization Test, 48 h, <i>Daphnia magna</i> , Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	3.1 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, <i>Scenedesmus subspicatus</i> , Static system, Fresh water, Experimental value, GLP)
Saccharin (81-07-2)	
LC50 fish 1	> 100 mg/l Test organisms (species): <i>Poecilia reticulata</i>
EC50 Daphnia 1	104.403 mg/l Test organisms (species): <i>Daphnia pulex</i>

12.2. Persistence and degradability

Cumene hydroperoxide (80-15-9)	
Persistence and degradability	Not readily biodegradable in water.
Saccharin (81-07-2)	
Persistence and degradability	Biodegradability in water: no data available.
epoxy resins, solids (25068-38-6)	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

Cumene hydroperoxide (80-15-9)	
BCF other aquatic organisms 1	9 (BCFWIN, Calculated value)
Log Pow	1.6 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Saccharin (81-07-2)	
Log Pow	0.91
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
epoxy resins, solids (25068-38-6)	
Bioaccumulative potential	Low potential for bioaccumulation (molecular mass >= 700 g/mol).

12.4. Mobility in soil

Threadlocker Red 120 0.34 fl oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Cumene hydroperoxide (80-15-9)	
Surface tension	28 mN/m (-9 °C)
Log Koc	1.6 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.

epoxy resins, solids (25068-38-6)	
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

Other adverse effects : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Dispose of as chemical waste in accordance with current local legislation.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Avoid release to the environment. Refer to manufacturer/supplier for information on recovery/recycling.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3082 Environmentally hazardous substances, liquid, n.o.s., 9, III
UN-No. (DOT) : UN3082
Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s.
Class (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 9 - Class 9 (Miscellaneous dangerous materials)



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241
DOT Symbols : G - Identifies PSN requiring a technical name

Threadlocker Red 120 0.34 fl oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- DOT Special Provisions(49 CFR 172.102) : 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.
146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.
173 - An appropriate generic entry may be used for this material.
335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s." UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging.
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees Celsius of the liquid during filling.
TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions(49 CFR 173.xxx) : 155
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : No limit
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : No limit
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
- Emergency Response Guide (ERG) Number : 171
- Other information : No supplementary information available.

Transportation of Dangerous Goods

- Transport document description : UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III
- UN-No. (TDG) : UN3082
- Proper Shipping Name (Transportation of Dangerous Goods) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
- TDG Primary Hazard Classes : 9 - Class 9 - Miscellaneous Products, Substances or Organisms
- Packing group : III - Minor Danger

Threadlocker Red 120 0.34 fl oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TDG Special Provisions

: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S.; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act". (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS. SOR/2014-306, 99 - (1) Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., may be handled, offered for transport or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means of containment and during transport. (2) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety. SOR/2014-306

Explosive Limit and Limited Quantity Index

: 5 L

Transport by sea

Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., 9, III
UN-No. (IMDG) : 3082
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class (IMDG) : 9 - Miscellaneous dangerous substances and articles
Packing group (IMDG) : III - substances presenting low danger
Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s., 9, III
UN-No. (IATA) : 3082
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.
Class (IATA) : 9 - Miscellaneous Dangerous Goods
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Cumene hydroperoxide (80-15-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	10 lb
Saccharin (81-07-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	100 lb

15.2. International regulations

Threadlocker Red 120 0.34 fl oz

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

CANADA

Cumene hydroperoxide (80-15-9)

Listed on the Canadian DSL (Domestic Substances List)

Saccharin (81-07-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources : Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013.

Full text of H-phrases:

H227	Combustible liquid
H242	Heating may cause a fire.
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H373	May cause damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.