

Product Description

Multi-Purpose Lubricant is a penetrating oil with high lubricity and protection against moisture and corrosion. Due to its unique formulation, it has high penetration power, acting directly on rust, eliminating noise, preventing assemblies, parts and metal threads from jamming.

Physical Properties

Color:	Lightly yellowish
Physical state:	Pressed liquid
Odor:	Characteristic
Solubility:	Insoluble in water
Boiling point:	>231°F
Density:	6.96 lb/gal
Internal pressure (Psi at 77°F):	53–67
Spraying rate:	≥ 95%

Instructions for use and handling

1. Shake can well before use.
2. Press trigger and apply product to the desired surface
3. let soak for several minutes.

Storage

Keep in a covered and well ventilated place (with a temperature below 122°F). Under these conditions, the product in its original and sealed packaging is warranted for 2 years since the date of manufacture.

General information

Do not expose or store this product above 122°F (risk of explosion).

Store in a well-ventilated place, at room temperature, away from sources of ignition. Covered, fresh, dry and ventilated area. Store the can in an upright position.

Before using the product, read the Safety Data Sheet (**SDS**).

Available packages

Tekbond offers 8 oz (180g) packaging.

IMPORTANT: The information contained in this Technical Data Sheet was obtained from reputable sources. Neither Tekbond nor its brands are responsible for the use of the information or for the use, application or processing of the product described herein. Users shall be aware of possible risks arising from improper use of the product. Material supplied by its exporter.