

# Permanent Spray Glue



## Product Description

Tekbond Permanent Spray Glue can be used for a variety of household or professional projects. Offers excellent transparency and quick drying time. Recommended for applications that require precision and high performance without waste.

## Physical Properties

<b>Solid content:</b>	17%
<b>Base:</b>	Synthetic elastomer
<b>Appearance:</b>	Transparent
<b>Spray pattern:</b>	Low mist, fine particle spray
<b>Bonding time on a surface:</b>	30 seconds - 20 minutes
<b>Bonding time on two surfaces:</b>	30 seconds - 30 minutes
<b>Extra strong bonding:</b>	Spray on both surfaces with a drying time of at least 30 seconds.

## Typical applications

Suitable for bonding paper, cardboard, fabrics, felt, foam, plastic, wood, painted wood, carpeting and other materials.

## Properties and benefits

- ❖ Excellent coverage power;
- ❖ Bonds a wide range of materials;
- ❖ Precise gluing without waste;
- ❖ Allows for positioning time;

## Instructions for use and handling

1. All surfaces to be bonded must be clean and free of dust, oil, grease and moisture.
2. Shake well before using.
3. Apply at room temperature between 69°F to 80°F (20°C to 27°C).
4. Hold the can upright when applying the adhesive.
5. Hold can between 5" to 8" from the surface to spray.
6. To avoid clogging, invert the can after use and press the valve until only the gas comes out.

## Restrictions on use

The PERMANENT SPRAY GLUE is not indicated for the following situations:

1. For all surfaces that remove oil, plasticizers or solvents;
2. It must not be applied on plastic material: Polyethylene, Polypropylene, Nylon and Teflon;
3. In case of painted surfaces, check the conditions of the same regarding possible peeling and, if necessary, sand the place of application;
4. For surfaces that have direct contact with food;
5. It cannot be used as a structural adhesive;

For further information and safe handling of this product, please refer to the Material Safety Data Sheet (MSDS).

## Available packages

Available in 10.7 oz (305g) cans.

## Storage

Store in a dry, cool place at temperature between 60°F to 82°F (16°C and 29°C).

**IMPORTANT:** The information contained in this Technical Data Sheet was obtained from reputable sources. Neither Tekbond nor its brands are responsible for the use of the information or for the use, application or processing of the product described herein. Users shall be aware of possible risks arising from improper use of the product. Material supplied by its exporter.