



Product Description

Recommended for professional and household use. Provides firmer and more efficient adhesion than ordinary white glues, thanks to its higher solids content. Use on porous materials, such as paper, cardboard, fabrics, pottery and wood. Ideal for interior projects such as home repairs, carpentry, construction, crafts and school projects. Non-toxic, transparent when dry and low odor.

Physical Properties

(Visual) appearance:	White liquid
Odor:	Low odor
Viscosity at 25°C:	18000 cps
Density at 25°C:	9.18 lb/gal
Solid content:	49%
Film aspect:	Transparent and flexible
Drying Time	24 hours for full strength
Storage life at 5 to 25°C:	21 months

Instructions for use and handling

1. Make sure that the parts to be bonded are clean and free of oil and dust.
2. Apply a uniform layer of the adhesive to one of the surfaces.
3. Bond the parts before drying the adhesive and press.

Application Tips:

For better results, avoid applying excess glue. Use brush or roller to spread the glue as needed.

Passes ANSI/HPVA type II water-resistance

Storage

Keep the product in a closed container and store it in a cool place at 41°F to 77°F, away from direct sunlight, excessive heat, sparks, flames; Keep it out of the reach of children and pets. To prevent contamination of unused product, do not return any leftover material in its original packaging.

General information

In case of contact with skin and eyes, wash with plenty of water, if symptoms persist, seek medical attention. For further information and safe handling of this product, please refer to Safety Data Sheet (**SDS**).

Available packages

- ✓ Plastic bottle: 8 fl oz, 16 fl oz & 32 fl oz

IMPORTANT: The information contained in this Technical Data Sheet was obtained from reputable sources. Neither Tekbond nor its brands are responsible for the use of the information or for the use, application or processing



DATA SHEET White Glue

Issued in: 03/2020

Revised in:
03/2020

of the product described herein. Users shall be aware of possible risks arising from improper use of the product. Material supplied by its exporter.