



Product Description

WOOD GLUE TEK BOND is a fast drying and strong bonding adhesive ideal for all wood projects. Provides a strong, durable bond for all types of wood, plywood, particle board etc.

Physical Properties

(Visual) appearance:	Slightly yellowish liquid
Odor:	Characteristic
Viscosity at 25°C:	110000 cps
Density at 25°C:	9.18lb/gal
pH at 25°C:	6.00–8.00
Application temperature:	+41°F to 113°F
Operating temperature:	-22°F to 194°F
Solid content:	43%
Film aspect:	Transparent and flexible
Storage life at 5 to 25°C:	21 months

Storage

Keep the product in a closed container and store it in a cool place at 41°F to 77°F, away from direct sunlight, excessive heat, sparks, flames; Keep it out of the reach of children and pets. To prevent contamination of unused product, do not return any leftover material in its original packaging.

Instructions for use and handling

1. Clean and dry surfaces to be bonded.
2. Apply a uniform layer of the glue to one of the surfaces.
3. Bond the parts and press and/or use clamp.

APPLICATION TIPS: For better results, avoid applying excess glue. Use brush or roller to spread the glue as needed.

General information

In case of contact with skin and eyes, wash with plenty of water, if symptoms persist, seek medical attention. For further information and safe handling of this product, please refer to Safety Data Sheet (**SDS**)

Available packages

- Plastic bottle: 8 fl oz and 16 fl oz.

IMPORTANT: The information contained in this Technical Data Sheet was obtained from reputable sources. Neither Tekbond nor its brands are responsible for the use of the information or for the use, application or processing of the product described herein. Users shall be aware of possible risks arising from improper use of the product. Material supplied by its exporter.